


# MACT Compliance Options



Discovering what's possible with calcium

May 7, 2015

# Dry Sorbent Injection Options for MACT




- DSI with FGT grade hydrated lime has proven effective at capturing SO<sub>2</sub> & HCl in both conventional boiler systems & cement plants.
- In challenging applications a High Reactivity or fast reacting hydrated lime may be required or desired.

# Hydrated Lime Types and Expectations


Hydrate	Target Mkt	Description	Annual tonnage
Regular	<ul style="list-style-type: none"> <li>• WWT</li> <li>• Construction</li> </ul>	<ul style="list-style-type: none"> <li>• Low surface area</li> <li>• Low purity</li> </ul>	1.2 X
Standard	<ul style="list-style-type: none"> <li>• Water treatment</li> <li>• Chemical</li> </ul>	<ul style="list-style-type: none"> <li>• Moderate surface area</li> <li>• High purity</li> </ul>	1.1 X
Flue Gas	<ul style="list-style-type: none"> <li>• Dry sorbent injection</li> <li>• Dry scrubbers</li> </ul>	<ul style="list-style-type: none"> <li>• High purity</li> <li>• High (&gt;20) surface area</li> </ul>	X
High React	<ul style="list-style-type: none"> <li>• Next generation for DSI and CDS</li> </ul>	<ul style="list-style-type: none"> <li>• High purity and surface area</li> <li>• Fast reactivity</li> </ul>	0.7 X

# HCl Reduction – CFB w/ Bag House




# HCl Mitigation – Industrial Boiler

- 135,000 lbs/hr stoker boiler; KY washed coal
- Fed ~ 40 ft before the bag house



- HCl control to below MACT levels with High Reactivity Hydrate


# 2013 FSI Testing FGT Hydrate (only one stone mill):



# DSI In Cement Manufacturing



# Cement Plant for HCl





# Typical Scrubber System in Cement

- Hydrated lime is mixed on site into a slurry
- Slurry fed through nozzles into the SO<sub>2</sub> scrubber
- In many systems the nozzles eroded &/or plugged - causing high maintenance costs.
- In the Midwest liquid systems froze, making compliance difficult & inconsistent (especially during the “Polar Vortex” in early 2014)




Could we get the same removal rates using **Dry** Sorbent Injection – and eliminate the challenges with handling a liquid slurry??

# Evaluation of Dry Sorbent Injection


- MLC supplied a temporary DSI feed system to a large US cement manufacture
- 2 feed locations were tested: the bucket elevator (before scrubber tower) & the ID fan (after the scrubber tower)
- Bucket Elevator location was more effective on SO<sub>2</sub> removal, ID Fan location was more effective on HCl




# Results: SO<sub>2</sub> Removal at Bucket Elevator



# Results: HCl Removal at ID Fan



# Results: FGT vs High Reactivity



# Conclusions:

- DSI with hydrated lime can allow SO<sub>2</sub> & HCl reduction for both industrial boilers and cement manufacturers.
- Depending on the application and the facilities goals, a High Reactivity Hydrate may allow better removal or lower costs.
- In cement scrubber towers, DSI gave comparable removal rates to feeding a liquid slurry of hydrated lime directly to the scrubber tower.

# Questions

**Pat Mongoven**

Business Development Manager – FGT  
pgmongoven@mississippilime.com

**Curt Biehn**

Manager, Marketing and Technical Services  
crbiehn@mississippilime.com

**Mark DeGenova**

Chief Chemist  
mgdegenova@mississippilime.com

**Eric Van Rens**

Vice President, Sales & Marketing  
ecvanrens@mississippilime.com

**Mississippi Lime Company**  
**3870 S. Lindbergh Blvd.**  
**Suite 200**  
**St. Louis, MO 63127**  
**www.mississippilime.com**



Discovering what's possible with calcium™