

Paper # 72

CCS Project with Alstom's Chilled Ammonia Process at AEP's Mountaineer Plant


EPRI-EPA-DOE-A&WMA
Power Plant Air Pollutant Control "MEGA" Symposium

R Bollinger
D Muraskin

August 31, 2010
Baltimore, MD



- **Project Overview**
- **CO₂ Storage Characterization & Design**
- **CO₂ Storage System Operations**
- **Alstom Chilled Ammonia Process**
- **Conclusions**
- **Q&A**



- **Goals for the Project**

- **Validate** Alstom's Chilled Ammonia Process
- **Integration** with CO₂ Sequestration
- Longer term **characterization** of storage reservoirs

- **Flue Gas Slip Stream from Mountaineer Plant**


- Equivalent to 20 MW (electric) from WFGD System

- **Capture and Store** ~100k metric tons of CO₂ per year


- **Project Milestones**

- Started engineering, planning, & permitting 3Q 2007
- Started construction 2Q 2008
- Captured CO₂ for first time Sep 1 2009
- Injected CO₂ for first time Oct 1 2009

- **Site characterization** and feasibility assessment conducted in 2003 by Battelle & Others under **DOE funded project**
- **Foundational work** for AEP's CCS program
- Identified Two(2) feasible injection formations for CO₂:
 - **Rose Run Sandstone** (AEP-2, 7800 ft)
 - **Copper Ridge B Zone** (AEP-1, 8200 ft)
- Characterization study found **thousands of feet of “Cap Rock”** to contain the stored carbon dioxide




- **Well Design** an important means to contain CO₂ in reservoir
 - Ex. AEP-2 in Rose Run Sandstone
- Similar in design to **wastewater injection wells** used in oil & gas industry
- **Type V** Underground Injection Control permit issued by WVa DEP
- **Multiple cascading well casings**, to provide isolation from:
 - Shallow freshwater
 - Intermediate zones containing coal seams, oil & natural gas
- **Stainless steel casing and CO₂ resistant cement deep injection well section**



Rose Run Sandstone- 116 ft total thickness, 30 ft porous sandstone



Hydraulic Core Tests 7763.5 ft	
Lithology	=
Sandstone	
Density	= 2.68
g/mL	
Porosity	= 9.1%
Permeability	= 36 mD



Data from Battelle



Hydraulic Core Tests 7775 ft	
Lithology	=
Sandstone	
Density	= 2.64
g/mL	
Porosity	= 10.4%
Permeability	= 49 mD



Hydraulic Core Tests 7819 ft	
Lithology	=
Sandstone	
Density	= 2.63
g/mL	
Porosity	= 11.5%
Permeability	= 36 mD



➔ Porosity & Permeability suggested adequate storage reservoirs

Beekmantown Dolomite 7210-7755 ft

Rotary Sidewall Core 7275 ft




Thin Section 7275 ft



Hydraulic Core Tests 7275 ft
Lithology = Dolomite
Density = 2.82 g/mL
Porosity = 0.38%
Permeability = <0.001 mD

Wireline Log 7100-7300 ft



Battelle Graphic

➔ Low Porosity & Permeability indicate excellent cap rock to maintain CO2 storage

MEGA Symposium – CCS Project with Alstom's CAP at AEP's Mountaineer Plant August 31, 2010 - P 7

Injection Well Monitoring


- A** - Flow rate, pressure, temperature
- Annulus pressure
 - Corrosion monitoring
 - CO₂ product analysis

Surface Leak Detection Methods

- B** – Shallow groundwater monitoring

CO₂ Tracking and Caprock / Confining Layer Monitoring Methods

- C** – Fluid sampling
- D** – Wireline logging
- E** – Pressure monitoring
- F** – Cross-well seismic survey




- Injectivity better than expected into AEP-1 Copper Ridge formation
- AEP-2 Rose Run slow to respond initially; better response recently
- Testing & Monitoring have confirmed CO₂ containment
- *Next steps*- To evaluate longer term reservoir behavior / storage capacity





- Project Overview
- CO₂ Storage Characterization & Design
- CO₂ Storage System Operations
- **Alstom Chilled Ammonia Process**
- **Conclusions**
- **Q&A**

SOLUTIONS DEVELOPED BY ALSTOM



**Oxy-combustion
(New + retrofit)**


**Post-combustion
(New + retrofit)**



- **Chilled Ammonia Process**
- **Advanced Amines**
- **Anti-Sublimation**

Chilled Ammonia Process Technology Features

- Energy efficient capture of CO₂
 - Utilizes ambient conditions / natural sources for flue gas cooling
- Can accommodate typical flue gas contaminants (SO_x, HCl, HF, NO_x)
- Flue gas exhaust conditions suitable for release to atmosphere
 - low ammonia slip
 - additional testing forthcoming
- High pressure regeneration
 - High purity CO₂ product, low moisture and ammonia
 - Reduced CO₂ compressor power
 - Lower regeneration energy, low vaporization of water from solvent
- Low cost and market stable reagent with potentially salable byproduct (ammonium sulfate) stream




**AEP Mountaineer
Product Validation Facility
Chilled Ammonia Process
New Haven, WV**

CAP Development Program Summary Development Plan



CALENDAR YEARS &
 DATES



Commercial Deployment in 2015



Field Pilot Program

- Operational June 2008
- 7700+ hours of operation on flue gas from PRB coal through completion of program in Oct 2009
- Proof of Concept technology validation:
 - 90% CO₂ capture efficiency
 - NH₃ slip from DCC2 (~5 ppm)
 - 99+% CO₂ purity; <10 ppm NH₃; < 2,000 ppm H₂O
 - Functional unit operations
 - Confirmation of process design tools

CO₂ Field Pilot at Pleasant Prairie

MEGA Symposium – CCS Project with Alstom's CAP at AEP's Mountaineer Plant August 31, 2010 - P 14



Karlshamn Power Plant (Sweden)



CAP Field Pilot



Field Pilot Program

- Operational Apr 2009
- 1500+ hours of operation on flue gas from sulfur fuel oil ongoing
- Proof of Concept technology validation:
 - 90% CO₂ capture efficiency
 - Flue gas NH₃ slip (~5 ppm)
 - 99+% CO₂ purity; <10 ppm NH₃; < 2,000 ppm H₂O
 - Functional unit operations
 - Confirmation of process design tools

AEP Mountaineer Product Validation Facility

Location	New Haven, WV
Capacity	100,000 tonnes CO ₂ /yr 110,230 tons CO ₂ /yr 275 tonnes / day
Size	~ 20 MWe 50,584 scfm
CO₂ Capture Efficiency	75%
CO₂ Storage	Deep geological formations
CO₂ Product	CO ₂ : 99.5+% H ₂ O: 600 ppmv
Upstream APC Equipment	ESP, WFGD, SCR, SO ₃ Mitigation
Start-Up	September 1, 2009
Fuel	Bituminous Coal
Reagent	Ammonium bicarbonate \ carbonate
Absorber Column	Packing
Regeneration Energy	Steam – turbine extraction. Integration of steam condensate not included
Byproduct	Ammonium sulfate




Alstom's Chilled Ammonia Process at AEP's Mountaineer Plant,

All pictures of the Mountaineer CO₂ Capture and Storage Project are the property of Alstom Power and/or AEP

MEGA Symposium – CCS Project with Alstom's CAP at AEP's Mountaineer Plant August 31, 2010 - P 16


The following CAP issues were identified during initial operation resulting in modifications to improve operability

- Utilization \ handling of solid reagent
- Operation of flue gas cooling coils
- Turndown of refrigeration system and CO₂ compressor
- Regenerator feed solution heat exchanger network
- Adjustments to accommodate transient power plant operation




- PVF operating hours: 4400+
- PVF capacity: 40-75%
- CO₂ captured: 19,000+ metric tons
- CO₂ injected: 14,000+ metric tons

- CO₂ removal efficiency above design value of 75%
- Flue gas measurements taken from on-line FTIR instrumentation
- Values verified by mass balance, existing plant CEMS, and field measurements
- Operating data reflects measurements at various conditions, reduced capacity




Conditions shown include variations in scrubbing solution strength and plant capacity

- High purity CO₂ product purity achieved on a consistent, stable basis
- Measurements obtained from on-line FTIR analyzer, consistent with field measurements
- Reported CO₂ purity obtained by difference from H₂O and NH₃ measurements



- Flue gas ammonia concentrations leaving the CAP maintained at low levels
- Flue gas ammonia measurements obtained using on-line FTIR
 - Initial on-line instrument inconsistent with field measurements
 - Sample port modifications made to improve on-line accuracy



Main objectives to be demonstrated in test campaign and validated with EPRI

- Energy consumption
- CO₂ removal efficiency
- CO₂ product quality
- System reliability

- The Chilled Ammonia Process has been operated at the bench scale, pilot and validation facilities. The plants have demonstrated:
 - CO₂ removal efficiency of 90%+
 - High purity CO₂ product (99.5%+)
 - Storage of CO₂ in geological formations
 - Ammonia emissions in the flue gas at desired levels
- Next steps for the AEP Mountaineer PVF
 - Implementation, tuning of modifications to achieve continuous, full load operation
 - Data collection and evaluation
 - Performance validation with EPRI
- AEP \ Alstom engaged in DOE funded commercial scale plant project

Mike Hammond

Project Engineer
American Electric Power
1 Riverside Plaza
Columbus, OH 43215 USA

Brian Sherrick

Project Manager
American Electric Power
1 Riverside Plaza
Columbus, OH 43215 USA

Gary Spitznogle

Chemical Engineering Manager
American Electric Power
1 Riverside Plaza
Columbus, OH 43215 USA

Mike Varner

Alstom Power, Inc.
Project Manager
1409 Centerpoint Blvd
Knoxville, TN 37932 USA

Fred Kozak

Alstom Power, Inc.
Business Manager CAP Technology
1409 Centerpoint Blvd
Knoxville, TN 37932 USA

Matt Cage

Alstom Power, Inc.
Project Engineer
1409 Centerpoint Blvd
Knoxville, TN 37932 USA

- **Project Overview**
- **CO2 Storage Characterization & Design**
- **CO2 Storage System Operations**
- **Alstom Chilled Ammonia Process**
- **Conclusions**
- **Q&A**

www.alstom.com


ALSTOM

- Designed to capture 100,000 tonnes CO₂/year
- Captured CO₂ is sequestered into two wells on the plant property
- Commenced engineering and permitting in Sep 2007
- Started construction 2Q 2008
- First CO₂ captured 1st of September, 2009
- Injection started 1st of October, 2009
- Technology Validation Program initiated with EPRI



Alstom's Chilled Ammonia Process at AEP's Mountaineer Plant,

All pictures of the Mountaineer CO₂ Capture and Storage Project are the property of Alstom Power and/or AEP



1. **Planned outage to support pilot modifications**
2. **Power Plant Forced Outage**
3. **Planned outage to support pilot modifications**
4. **Thanksgiving + Planned outage to support modification**
5. **Christmas Holidays**
6. **Power Plant Forced Outage**
7. **Planned outage for pilot maintenance**
8. **Unplanned outage for pilot maintenance (chiller)**
9. **Unplanned outage for pilot maintenance (stripper)**
10. **Planned outage to support pilot modifications**
11. **Outage - Regenerator Level Transmitter**

Total operating hours - 7,717
Over 65% Availability

CAP Development Program Main Partnerships & Projects Portfolio

Chilled Ammonia	Pleasant Prairie, WI (US) – Coal	5 MWt		Operational Jun08 to Oct09
	Karlshamm (Sweden) – Oil/Gas	5 MWt		Operating since fall 2008
	Mountaineer WV (US) – Coal	54 MWt		Operational since Sept 09
	Mongstad (Norway) – Gas	40 MWt		Engineering on going
	Pioneer (Canada) – Coal	>150MWe		Planned start-up 2015
	Commercial scale (US) – Coal	>200MWe		Planned start-up 2015

Pilots in operation

Tests completed

* Project will include carbon sequestration

Projects in different regions with different fuels