


The Siemens logo is displayed in a bold, teal, sans-serif font in the upper right corner of the slide.The text "Intelligent Energy Solutions" is written in a bold, black, sans-serif font and is contained within a white rectangular box in the upper left area of the slide.The title "HRSG Operational Challenges and Siemens' Solutions" is centered on the right side of the slide in a large, bold, black, sans-serif font.The text "Gary Gong Ph.D P.E." is positioned below the title on the right side of the slide in a bold, black, sans-serif font.The contact information "Siemens Energy Inc", "4400 N Alafaya Trl", and "Orlando, FL 32766" is listed below the name on the right side of the slide in a bold, black, sans-serif font.The copyright notice "© Siemens Energy, Inc. 2010" is located in the bottom right corner of the slide in a white, sans-serif font.

Agenda

Challenge: HRSG Design for today's Flexibility

Solution: Flex-Plant HRSG Design

Fossil Products and Solutions Market Drivers

Shaping Renewables



Competitive in Changing Markets




SGT6-5000F



Flex-Plant 10



Flex-Plant 30



Improve Efficiency/Output



Eliminate / Reduce Water Consumption



Reduce Emissions



Two Primary Concerns for Fast Start HRSG

Thermal Stress on High Pressure Steam Drum

- Severe operating conditions require thick component wall
- Fast startup produces high thermal gradient in wall
- Component fails after fatigue life is consumed

Drum Level Control

- Gas turbine startup produces rapid boiling in evaporator
- If water level in drum rises too fast during flash, water carryover may occur
- Typical response is to trip or slow GT load ramp
- Integration of feed water systems highly complex


© Siemens Power Generation, Inc. 2007. All rights reserved.

SCC6-5000F 1x1 Flex-Plant™ 10

- One pressure CCPP for peak to intermediate

SIEMENS

SGT6-5000F ➔ Flex-Plant 10



The best solution for economic peaking to intermediate duty dispatch

- 275 MW, 48.8% efficiency
- Non-spinning reserve/ancillary service
 - 10-minute start gas turbine
 - 30 MW/min load regulation
- Lowest total emissions
- Lowest water consumption
- Low gas pressure requirements



Low Capacity Factor Peaking

Intermediate Duty

High Capacity Factor Continuous Load Duty

One Solution - Flex-Plant HRSG Drum Design

- HP Drum: Moisture Separation occurs in separator instead of drum, which reduces drum size.
- Small drum for primary steam separation and water steam separators.
- Large capacity emergency blowdown to condensate system to manage severe transients



Flex-Plant HRSG Transient Analysis

Purpose:



- Develop input data for lifetime analysis
- Evaluate system response in transient events
- Analyze behavior for emissions performance

Analyses:

- GT startup / shutdown
- FW pump trip
- ST trip

Results:

- Full pressure & temp in < 20 min
- Impact of increased ramp rate has been minimized
- All transient flow control criteria fulfilled



Critical Component Lifetime Analysis

Purpose:

- Identify critical components
- Verify design meets lifetime criteria

Analyses:

- 200 Hot / 50 Warm / 10 Cold starts per year
- FE analysis of critical components
- Creep analysis – API 530 & ASME III, Div. 1
- Fatigue analysis – EN 12592-3

Results:

- Fatigue consumption meets design life reqt's
- Magnetite stresses below EN 12592 limits
- Relationship of fatigue life to start profile





FIG. T-1420-2 CREEP-FATIGUE DAMAGE ENVELOPE





SCC6-5000F 2x1 Flex-Plant™ 30



Three pressure RH for intermediate to continuous

SGT6-5000F  Flex-Plant 30



The best solution for intermediate to continuous duty needs

- 618 MW, 57+% efficiency
- Faster start-up times than traditional CC
- Low start-up emissions
- Low start-up fuel consumption


Low Capacity Factor
Peaking

Intermediate Duty

High Capacity Factor
Continuous Load Duty


Benson HRSG

Conventional Drum vs. Benson OTSG



Drum-Type

- Vertical tube modules in horizontal gas path
- Thick-walled HP drum
- Natural circulation principle



Benson OT


- Vertical tube modules in horizontal gas path
- Replace drum with thin-walled components
- Maintains natural circ flow characteristics

Copyright © Siemens Energy, Inc. 2009. All rights reserved.

Benson HRSG

Superheater Designs

1. Single row of tubes between headers
2. Finned tubes with no bends
3. Smaller diameter headers with multiple header connections (thermal stress reduced by 60%)
4. Seamless tubes



**OT
Design**

**Conventional
Technology**

Summary

- Identified primary concerns for fast start of HRSG's
- Worked with key suppliers to establish & verify design
- Conservative, thorough analysis methodologies
- Transient behavior understood and can be controlled
- Analysis shows positive results for design life