

1. I am adding an SCR to my plant. Should I upgrade my existing fans, add a booster fan or install a new fan? How can I decide?

Considerations:

- Pressure required: High pressure requires high tipspeed → High wheel stress, Low specific speed (possibly lower efficiency) noisier
- Space available
- Time available for change-over
- Control – One fan easier than 2 in series
- Is current foundation OK for upgraded fan?
- Ductwork connections

3. What are the suggested maintenance operations and frequency to maintain fan efficiency and lengthen the life?

- Efficiency: Dampers/VIV's clean and operational, Rotors clean and not worn, wheel to inlet cone clearance
- Life: Lubrication, alignment, monitor bearing temperature and vibration
- Consult the fan supplier's O&M Manual!

4. Which is the best type of fan for each application in a power plant (centrifugal, variable pitch or axial) and why?

- Specific speed – axials typically higher (high flow/low pressure)
- efficiency
- turn-down range
- particulate load – erosion/build-up
- Ref. AMCA Publication 801, Specification Guidelines

5. My flue gas has a high particulate load. What is the best way to improve the life in a highly abrasive environment?

- Velocity related – exponentially
- DWDI vs. SWSI
- Low speed vs. High speed
- Blade profile
- Liners: AR plate/ Chromium carbide/tungsten carbide/ceramic
Wheel, Casing, Inlet boxes, Inlet cones

6. How can I decide whether a fixed speed fan with dampers or a fan with a variable speed motor for fan control is best for my application?

- Initial cost vs operational cost
- Amount of turn-down


Robinson Industries, Inc.
Fan : 83" x 14.38" FRD SWSI
For : Basic Fan Laws I

Fan Speed : 1180 RPM
Temperature : 70°F
Density : 0.075 LB/FT³

Date : 02/02/1999
Quote Number : 123456
RII FO # : 123456

Example:
Inlet
Louvered
Damper
Control:
Turndown
condition
requires 880
BHP

Note: Inlet
P(s) Ratio = 0



BHP

FF : 1
SE : 1
TF : 1

ROBINSON INDUSTRIES, INC.

FAN : 83" x 14.38" FRD


FOR : Basic Fan Laws I

FAN SPEED : 840

TEMP. : 70

DENSITY : 0.075

Example:
Speed
Control:
Same
turndown
condition
requires 450
BHP



7. How can I optimize the performance of my fans to improve efficiency?

- Field test – Establish baseline current performance
- Control range required
- Consider rotor retrofit – Performance must be confirmed via lab model prototype test
- Don't neglect mechanical and other operational concerns

8. What speed should I specify? Why?

High speed:

- smaller
- lower cost
- higher N_s , higher efficiency(?)
- higher velocities
- higher wear
- higher bearing peripheral speed


9. Do I need to specify an overspeed test for the fan rotor?

- The end user can feel more comfortable knowing that the rotors have been tested at speeds in excess of the actual maximum operating speed.
- Inspection of the rotor welded joints before and after testing (using non-destructive inspection techniques) provides further proof that the rotor can tolerate such high stress levels without any cracks developing.



What balance quality grade should I specify?

➤ ANSI S2.19 Grade G2.5 is appropriate for most fan applications in the power industry. Ref. AMCA/ANSI 204



11. What source would you recommend for learning about basic fan performance parameters and definitions?

➤ AMCA International (Air Movement and Control Association) 801, 99, etc.


AMCA Publication 801-01 (R2008)

Industrial Process/Power Generation
Fans: Specification Guidelines



**AIR MOVEMENT AND CONTROL
ASSOCIATION INTERNATIONAL, INC.**

The International Authority on Air System Components



12. What happens if I throttle my fan too much with the inlet control dampers?

What if you squeeze me too hard?



+ \$\$\$ Energy

Reduced
Control

Aerodynamic

Instability

Increased
Vibration

Potential
Mechanical
Failures

13. What factory testing and analyses should be specified?

Options include:

- Wheel stress FEA
- Fatigue analysis
- Wheel modal analysis
- Torsional
- Lateral
- shop balance
- Impeller overspeed test
- CFD