





The GMCS Hg Control System

Provided by W.L. Gore and URS Supported by EPRI


Presentation to:

Web Forums

August 2, 2012

✓Summary

Technology Overview
 Experience
 Performance
 Installation Approach
 Path Forward








Gore SPC Hg Control System



Passive fixed bed device

✓ Performance

- × 90+ percent Hg removal
- × 60+ percent SO₂ removal
- Not sensitive to Hg concentration
- × Not sensitive to Hg speciation
- × No boiler additive injection
- No activated carbon injection
- × No impact on the fly ash quality
- × No impact on gypsum quality
- No concerns regarding Hg reemission
- × Fuel flexibility
- × Very low waste generation
- Life expectancy 3 to 9 years.




11:45

Summary
 Technology Overview
 Experience
 Performance
 Installation Approach

✓ Path Forward

Copyright © 2012 URS








Gore SPC Hg Control technology



Fixed Bed Sorbent Polymer Composite (SPC) material


- 1 ft wide tape of composite fluoropolymer membrane
- Modularized
- Unique physical-chemical nature of the SPC material
 - Efficiently captures both elemental and oxidized mercury Hg
 - SO₂ is converted into sulfuric acid and expelled to SPC material's outer surfaces
 - Very high capacity for mercury storage
 - Does not require regeneration





Modular Structure








CONFIDENTIAL - This document is proprietary and competitively sensitive. Any disclosure, copying, or use of it is strictly prohibited.


Summary
 Technology Overview
 Experience
 Performance
 Installation Approach
 Path Forward







Plant Yates Demonstration (2010)



Creative Technologie



Gorgas Pilot Plant



- ✓3,000 cfm slip stream
- Post-scrubber installation
- Full-size modules, single stack of 4
- ✓ Start-up June 2012
- Demonstration of longterm stability of mercury and SO₂ removal postscrubber
 - Planned operation for at least 1 year








NW Utility Pilot Plant



Pilot plant
 installed during
 July outage
 Will operate for
 six months to a
 year

 One module (out of four) demonstration starting March 2013

 ✓ Fullscale installation in 2014





Coal Creek Pilot








Coal Creek Results

13 to 14 fps flue gas velocity
40 lbs / TBtu of Hg
3 Layers of modules
Hg removal 85%
SO₂ removal 63%
Pressure drop 0.76 inches




Summary
 Technology Overview
 Experience
 Performance
 Installation Approach
 Path Forward





Average Removal Efficiency








Insensitive to Variable Inlet Concentrations






Significant changes in mercury inlet concentrations do not require any adjustments or changes to the modules



Lifetime Projections¹





¹ Site specific, depends on Hg concentration, number of GMCS modules and pounds of SPC per module



Summary
Technology Overview
Experience
Performance
Installation Approach
Path Forward





Installation in a Wet FGD Scrubber



Wet FGD Installation

- Downstream of mist eliminator
- Sulfuric acid weeping may be key to why the SPC modules stay clean

Proposed installation approach


- Use second ME support grid to hold SPC modules
- Use the first ME support grid to support a dual layer ME
 - Munters DV210
 - Koch Flexipeak

Modular design

- × 2 to 4 layers
- Less than 1 inch of pressure drop


✓ Long life

Last for multiple outage cycles





ME Options- One Support Structure




Munters DV210

Koch Flexipeak



Typical Installation








Installation Close-Ups






Unmodified DV210 Flexipeak



Summary
 Technology Overview
 Experience
 Performance
 Installation Approach
 Path Forward







Path Forward



✓ Pilot plant status

- × 2009 Three pilot plants at cement plants
- × 2010 Plant Yates ex-situ
- × 2012 Gorgas ex-situ
- × 2012 NW Utility in-situ

✓ Commercial by 4 Qtr, 2012

- Seeking early adopter sites
- Attractive discounts will be offered
- One module demonstration
 - × 2013 (March) NW Utility
- Project duration
 - × 6-8 months

